



Radio Monitoring

Airborne Monitoring

LS OBSERVER

Airborne Monitoring Unit (AMU) 132s



TECHNICAL DETAILS **LS OBSERVER AMU 132s**

RF Characteristics		
RF Characteristics	Frequency range	20 MHz to 32 GHz
	Max. input level	-140 dBm @ 1 GHz/ +20 dBm, 0 VDC
	Instantaneous bandwidth	scan mode only

Measurement Functionalities		
Measurement Functionalities	RF scanning	yes
	Direction Finding (DF)	yes (AoA calculation from 360° turn)
	Geolocation	yes (triangulation of sequential DF measurements)
	Demodulation	no
	IQ recording	no

Antenna Characteristics		
Antenna characteristics	Lower frequency range	20 MHz to 400 MHz (loop antenna)
	Medium frequency range	400 MHz to 1300 MHz
	Higher frequency range	900 MHz to 6 GHz
	Microwave range	1 GHz to 18 GHz and 18 GHz to 32 GHz (horn antenna)

Operational Parameters of the UAS		
Operational Parameters of the UAS	Platform	COL-X8 multi-rotor with removable carbon arms
	Propulsion	electrical, 4x2 motors 300 kW
	Propeller size	18" x 5.5" (standard configuration)
	Max. flight height ¹	500 m, 80 m with tether kit

Powering of the UAS		
Powering of the UAS	Battery version	
	Tether supply	
	Typ. flight time	up to 15 minutes with 4 x 4500 mAh batteries
	Power input	unlimited ²
Powering of the UAS	AC mains 120-240 VAC	
	Power monitoring	via telemetry
power monitoring with acoustic alarm, automatic short term LiPo Backup		

Communication		
Communication	Battery version	
	Tether supply	
	Aircraft control frequency	2,4 GHz
	Aircraft telemetry frequency ³	433 MHz / 868 MHz / 900 MHz
Communication	Live measurement data	via WiFi
	via CAT-6 Ethernet cable	

Environmental Parameters		
Environmental Parameters	Temperature range	
	Weight	
	Dimension in mm (W/H/D)	

¹ depending on weather conditions and payload

² maximum flight time limited by other factors than powering

³ depending on country regulation

For further information, please visit our website www.LStelcom.com or contact Info@LStelcom.com.